

GREENTARP[®]



GreenTarp Pile Seal Application Guidelines

Recommended Equipment:
Mechanical Mixing Hydro Mulching System
Preferred Spray Nozzle: BEX F50500 or Jett 50500

Application Guidelines

Prepare the material to be applied so as to compact and minimize ridges
Mix recommended quantity of GreenTarpSM mulch and BT-PSC-G chemical
(Ratio can vary based on slope, weather and desired longevity)

33.2 Gallons of BT-PSC-G/acre
29.8 Bags of GreenTarpSMulch/acre
3746 Gallons of water

Best to apply from the top of pile down to bottom. Avoid wet conditions when applying. Product requires 24 hours to dry.



EXAMPLE of Solution Mixture



EXAMPLE of Hydro Seeder Sprayer

APPLICATIONS

- » Coal / Coke / Ore Stockpiles
- » Fly Ash Sites
- » Mine Operations
- » Quarry Operations
- » Haul Road Berms
- » Power Plants
- » Construction Sites
- » Steel Mills
- » Soil Stabilization
- » Land Reclamation
- » Waste Materials
- » Ground Covers



Final Application Consistency



Before Application



After Application

BENETECH
2245 Sequoia Dr. #300
Aurora, IL 60506

+1 (630) 844 -1300
info@benetechusa.com
www.benetechglobal.com

