BENETECH. «

SIMPLE INSTALLATION

Simple Slide Flat Carrying Idlers

Benetech's Simple Slide Flat Carrying Idlers allow for safe and simple installation and maintenance, while providing optimal belt support for the top carry side of the belt. The compact size of the frame allows for easy replacement.

FEATURES

- Available in standard or wide base frames
- CEMA C, D, & E
- Belt widths 24-60 in.
- For purchase as frame alone, or with rollers
- Single roller to carry belt on the flat top side of the belt
- Capable of servicing from either side of the belt by releasing two (2) bolts to remove roller cartridge
- Great for areas to inspect the belt making maintenance and visibility easier
- Can be customized to fit any idler manufacturers' rollers



KEY BENEFITS

- Can be serviced by one person from one side of the belt
- Rollers support the belt to prevent stretching, sagging, and failure
- No need to raise belt to replace roller
- Reduces safety risks and allows quick and easy roller removal or maintenance



BISAS	048 <mark>FLT</mark>	A 1 (С 5 Ѕ М	ΡΒ
BENETECH IDLER SLIDE-OUT F = Frame Only	BELT WIDTH FLAT	CH 1= C, D L 2 = F	CEMA CLASS & ROLL DIAMETER	BENETECH BLUE
BASE WIDTH S = Standard W = Wide Base		ROLLER TYPE S = Steel I = Impact	FRAME MATERIAL M = Mild Steel S = Stainless	P = Paint U = Unpainted G = Galv. (hot dip)



+1 (800) 843-2625 BenetechGlobal.com



©2025 Benetech, Inc. Issue: 2025-01