BENETECH®
SAFE MATERIAL HANDLING SOLUTIONS

Conveyor Idlers

Highest Quality. Advanced Sealing System.

Replacement Rollers
We offer the highest quality replacement roller for steel, impact, and return rollers. Designed with a triple labryinth seal our advanced sealing system provides optimal performance of the shaft, bearings, and sealing system.

Troughing Idlers - Standard & Impact CEMA C & D
Benetech's troughing idlers are used to transition from an impact area or load zone. They can also be used to transition from a flat pulley area, picking or feeding area. Meeting all CEMA requirements and available in standard or impact, belt widths 24-72", and troughing angle's of 20, 35, & 45 degrees.

Return Idlers - CEMA C & D
Benetech's return idlers are used to carry the belt back to the tail pulley after the load has been dumped at the head pulley. Designed to meet CEMA standards, and available in standard or impact, belt widths 24-72".

Benefits

- Sealed for life bearings
- Available in all CEMA classes
- Advanced sealing system
- CEMA class C, D, or E

Idlers

BIS-35 C5 -30SB

Benetech

Idler/Roll

I	Idler Assembly
R	Roll

Idler/Roll Type

S	Steel Equal Length	IR	Impact Return
I	Impact Equal Length	VR	V Return
R	Return	IVR	Impact V Return
F	Flat Idler		

Angle

10	35
15	45
20	

CEMA Class

B	D
C	E

Belt Width

SB	Sealed Ball Bearing
TR	Tapered Roller Bearing
RB	Regreasable Bearing

Belt Width (in)

24	54
30	60
36	66
42	72
48	

Roll Diameter (in)

4

5

6

Rollers

BRS- C5-30SB

Benetech

Idler/Roll

I	Idler Assembly
R	Roll

Idler/Roll Type

T	Steel Equal Length	IR	Impact Return
I	Impact Equal Length	VR	V Return
R	Return	IVR	Impact V Return
F	Flat Idler		

CEMA Class

B	D
C	E

Belt Width

SB	Sealed Ball Bearing
TR	Tapered Roller Bearing
RB	Regreasable Bearing

Belt Width (in)

24	54
30	60
36	66
42	72
48	

Roll Diameter (in)

4

5

6

BENETECH
2245 Sequoia Dr. #300
Aurora, IL 60506

+1 (630) 844 -1300
info@benetechusa.com
www.benetechglobal.com

Troughing Idler © Benetech, Inc. 012022